FIRE HOSE UL FM 300 PSI ATLANTIC USA

Attack Hose – DUZ Series



Features

This type of durable hose is Nitrite rubber covered hose, and along with high tensile strength polyester reinforcement for ma ximum durability and flexibility.

- Ribbed Nitrite rubber cover greatly increases abrasion resistance and provides long service life.
- Smooth Nitrite rubber liner minimum pressure drop.
- Hose remains flexible to temperatures as low as -4°F (-20°C) and is resistant to ozone, oxidation, and most chemicals or petroleum products.
- Polyester and/or Nylon reinforcement, tightly woven, twill weave resists puncture.

Technical Data

I.D.		SERVICE TEST PRESSURE	BURST PRESSURE
Inch	mm	Psi	Psi
1-1/2”	38	17/250.21/300	51/750.63/900
1-3/4”	45	17/250.21/300	51/750.63/900
2”	50	17/250.21/300	51/750.63/900
2-1/2”	65	17/250.21/300	51/750.63/900
3”	75	17/250.21/300	51/750.63/900

Construction: Nitrite rubber cover and liner. Polyester and/or Nylon reinforcement.

Application: Municipal fire fighting, industrial fire fighting, In- Plant fire protection. Meet and exceed UL 19 standard and BS6391 standard.

Color: Yellow, red, other colors on request.

Couplings: on request.

Standard Length: 50′(15m), 100′(30m), other length on your request.

Temperature Range: -4°F to 175°F(-20°C to 80°C), other temperature on request.