海神牌
HAISHENPAI

EPDM衬里消防水带

EPDM Fire Hose



产品特点：Features

重量轻，结构紧密，耐腐蚀，耐气候，耐臭氧，
抗霉变，抗紫外线,使用寿命长
Light weight, construction tightness,corrosion resistance, Weather resistance, Ozone resistance,Mildew resistance, UV resistance and long serving life.

压力要求：Pressure Required

口径 Diameter (inch/mm)		工作压力 Working Pressure (Bar)	Mpa	Psi)	爆破压力 Bursting Pressure (Bar)	Mpa	Psi)	备注 Remark
1"	25	13-25	1.3-2.5	190-365	39-75	3.9-7.5	570-1090	
1-1/4"	32	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
1-1/2"	38	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
1-3/4"	45	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
2"	52	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
2-1/2"	64	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
2-3/4"	70	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
3"	75	8-25	0.8-2.5	120-365	24-75	2.4-7.5	350-1090	
4"	102	8-16	0.8-1.6	120-235	24-48	2.4-4.8	350-700	
5"	127	8-13	0.8-1.3	120-190	24-39	2.4-3.9	350-570	
6"	152	8-13	0.8-1.3	120-190	24-39	2.4-3.9	350-570	

注：UL/FM认证水带，工作压力为250Psi; 最小爆破压力为750Psi. MED认证水带，工作压力为15BAR,最小爆破压力为45Bar,一种有红色涂层，另外一种没有涂层
P.S: For UL/FM approved fire hose, the working pressure is 250Psi,Burst pressure is 750Psi. For MED fire hose, the working pressure is 15bar, burst pressure is 45bar. With red coating or without coating.

应用范围：Application

消防；船舶；石油；化工；农业；矿山等
Fire-fighting, Shipping, petroleum, Chemical industry, Agriculture, Mining.

可供颜色：Color

带坯颜色白色,也可染成黄色或红色，或者根据客户的要求定制颜色
White,yellow, red,or as per customer's instruction

生产标准：Standard

GB6246，MED，EN14540，FM，UL

标准长度：Standard Length

10M至40M
10M up to 40M

产品构造：Constructions



使用热熔胶粘合剂，特点是重量轻，粘结力好
Properties to use Hot Melt : Light weight, good adhesive strength.



使用橡胶作为粘合剂的特点是，弹性更好，耐热性更好
Properties to use Rubber backing adhesive: more flexible and has higher heat resistance than other hoses using other adhesive.