ATLANTIC USA



FEATURE

A single jacket 100% filament polyester hose intended for interior protection and occupant use applications in buildings and plants. Lightweight and compact, Rack Hose-FBX is lined with TPU elastomer, and replaces unlined linen hose. FBX rack hose has a service test pressure rating of 232 PSIG (1600 kPa) and is approximately half the weight of conventional rubber lined single jacket hose.Rack hose is available folded for standard pin racks in 50' (15m), 75' (22.5m), and 100' (30m) lengths. Specify folded, coiled, or number of pins for rack.

UL FM APPROVED

PRESSURE REQUIREMENT

I .D. (Inch/mm)		Working Pressure (Bar/Psi)	Burst Pressure (Bar/Psi)
1-1/2"	38	10/150FM,14/200, 16/232FM	30/450,42/600,51/750
2-1/2"	65	10/150FM,14/200,17/250FM	30/450,42/600,51/750

APPLICATION

Building Protection
Wash Down

COUPLINGS AVAILABLE

Aluminum & Brass N H / N S T or I P T, Aluminum S t o r z ,Instantaneous coupling etc.

COLOR

The standard color for ATLANTIC USA is white. Other colors available with our innovative Wisentec™ abrasion resistant coatings are red, yellow, orange, blue, green and tan. Provides water repellency, abrasion, oil and chemical resistance. Color will be uniform throughout the length of each hose. The cost for color coating is additional.



STANDARD

Meets or exceeds FM and NFPA 1961 specifications.

STANDARD LENGTH

50', 75', 100'.

CONSTRUCTION

Filament polyester as warp and weft ,T.P.U. inner liner.